



RADICAL DEFENSE

CAGE: 8RC72 » DUNS: 043893696

CALIBER 5.56

LENGTH 5.0"

CS5 COMPACT SUPPRESSOR

3D printed monolithic design using a nickel based Super Alloy Haynes 282, the CS-5 is one of the most durable suppressors on the market to date. The CS-5 is capable of sustained full-automatic fire while providing operators with sound, thermal, and flash mitigation. A semi-auto rated version is also available in Ti6Al4V.

The CS-5 utilizes a forward venting monolithic design controlling cyclic rate while the assist ports reduce back pressure. The CS-5 is protected by a high-temp Cerakote coating, providing protection and a higher level of concealability. Alphatek Alphashield IR Reflective coating available

- Complete Signature Reduction
- Heat Resistant 3D-Printed Design
- Minimal Point-of-Impact Shift

Available in Tan or black

BREATHABLE TECHNOLOGY™



PRODUCT DETAILS

Specifications subject to change

CALIBER	5.56 NATO
MATERIAL	Haynes 282 or Ti64
COATING	Alphatek Alpha Shield IR
ATTACHMENT	1.375-24 HUB Mount

SUPPRESSOR*	WEIGHT	LENGTH	DIAMETER	HUB MOUNT*	WEIGHT	LENGTH
	19 oz / 14 oz (Ti)	5.0 in	1.78 in		2.61 oz	.280 in
0.53 kg / 0.39 kg	127 mm	45.21 mm	73.92 g	7.11 mm		

*Weights and dimensions may vary based on manufacturing tolerances.

SKU	UPC
CS5	814034027526
CS5 Ti	814034028301

FLAT FRONT PLATE DESIGN



Ti MODEL IN BLACK FINISH



KFM TAPER LOCK FLASH HIDER / RD HUB MOUNT INCLUDED



This document contains privileged and/or confidential information belonging to Radical Defense and is intended only for the use of the intended recipient. In addition, it may contain technical data as defined in the International Traffic in Arms Regulations (ITAR) 22 CFR 120.10. Export of this material is restricted by the Arms Export Control Act (22 U.S.C. 2751 et seq.), as well as other laws, and it may not be exported or transferred to non-U.S. persons without prior written approval from the U.S. Department of State.