



RADICAL DEFENSE

CAGE: 8RC72 » DUNS: 043893696

CALIBER 7.62

LENGTH 7.75"

SASS SUPPRESSOR

3D printed monolithic design using a nickel based Super Alloy Haynes 282, the SASS is one of the most durable suppressors on the market to date. The SASS is capable of sustained full-automatic fire while providing operators with sound, thermal, and flash mitigation. A semi-auto rated version is also available in Ti6Al4V.

The SASS utilizes a forward venting monolithic design controlling cyclic rate while the assist ports reduce back pressure. The SASS is protected by a high-temp Cerakote coating, providing protection and a higher level of concealability. Alphatek Alphashield IR Reflective coating available.

- Complete Signature Reduction
- Heat Resistant 3D-Printed Design
- Minimal Point-of-Impact Shift

PRODUCT DETAILS

Specifications subject to change

CALIBER	7.62 NATO
MATERIAL	Haynes 282 or Ti6414V
COATING	High Temp Cerakote or Alphatek Alphashield IR
ATTACHMENT	1.375-24 HUB Mount

SUPPRESSOR	WEIGHT	LENGTH	DIAMETER
	25.5 oz / 17.0 oz (Ti)	7.75 in	1.75 in (Max OD) / 1.6 in (Min OD)
	0.72 kg / 0.48 kg	196.85 mm	44.45 mm / 40.64 mm

RD HUB MOUNT	WEIGHT	LENGTH
	2.61 oz	.280 in
	73.92 g	7.11 mm

SKU	UPC
SASS762	814034028394
SASS762Ti	814034028400

BREATHABLE FRONT PLATE DESIGN



MODULAR HUB MOUNT

KFM TAPER LOCK FLASH HIDER / RD HUB MOUNT INCLUDED



This document contains privileged and/or confidential information belonging to Radical Defense and is intended only for the use of the intended recipient. In addition, it may contain technical data as defined in the International Traffic in Arms Regulations (ITAR) 22 CFR 120.10. Export of this material is restricted by the Arms Export Control Act (22 U.S.C. 2751 et seq.), as well as other laws, and it may not be exported or transferred to non-U.S. persons without prior written approval from the U.S. Department of State.