

## LS-3 SUPPRESSOR

Caliber: .300 Blackout

3D printed monolithic design using a nickel based Super Alloy Haynes 282, the LS-3 is one of the most durable suppressors on the market to date. The LS-3 is capable of sustained full-automatic fire while providing operators with sound, thermal, and flash mitigation. A semi-auto rated version is also available in Ti6Al4V.

The LS-3 utilizes a forward venting monolithic design controlling cyclic rate while the assist ports reduce back pressure. The LS-3 is protected by a high-temp Cerakote coating, providing protection and a higher level of concealability. Alphatek Alphashield IR Reflective coating available

PRODUCT DETAILS		
SKU#	LS3 or LS3TI	
CALIBER	.300 Blackout	
MATERIAL	Haynes 282 or Ti6Al4V	
COATING	High Temp Cerakote or Alphatek Alphashield IR	
ATTACHMENT METHOD	1.375-24 Hub Mount	
SIGNATURE REDUCTION	Flash Sound Ground Disturbance Thermal	

## BREATHABLE TECHNOLOGY

MEASUREMENTS	imperial	metric
LENGTH	7.5 in	19.05 cm
WEIGHT	17.5 oz Haynes	.50 kg
	8.6 oz Ti64	.25 kg
DIAMETER	1.6 in	4.06 cm



## KFM TAPER MOUNT FLASH HIDER AND 13/8"X24 HUB ADAPTER INCLUDED



