



CAGE: 8RC72 DUNS: 043893696

LS-5 SUPPRESSOR

Caliber: 5.56 NATO

3D printed monolithic design using a nickel based Super Alloy Haynes 282, the LS-5 is one of the most durable suppressors on the market to date. The LS-5 is capable of sustained full-automatic fire while providing operators with sound, thermal, and flash mitigation. A semi-auto rated version is also available in Ti6Al4V.

The LS-5 utilizes a forward venting monolithic design controlling cyclic rate while the assist ports reduce back pressure. The LS-5 is protected by a high-temp Cerakote coating, providing protection and a higher level of concealability. Alphatek Alphashield IR Reflective coating available

PRODUCT DETAILS


SKU#	LS5 or LS5TI
CALIBER	5.56 NATO
MATERIAL	Haynes 282 or Ti6Al4V
COATING	High Temp Cerakote or Alphatek Alphashield IR
ATTACHMENT METHOD	1.375-24 HUB Mount
SIGNATURE REDUCTION	Flash Sound Ground Disturbance Thermal

BREATHABLE TECHNOLOGY™


MEASUREMENTS*

	imperial	metric
SUPPRESSOR LENGTH	7.0 in	17.78 cm
SUPPRESSOR WEIGHT	20 oz Haynes	.55 kg
	10.5 oz Ti	.30 kg
SUPPRESSOR DIAMETER	1.75 in	4.45 cm

Suppressor pictured with factory installed HUB mount



KFM TAPER LOCK FLASH HIDER AND 1.375-24 RD HUB MOUNT INCLUDED



RD HUB MOUNT

MEASUREMENTS*

	imperial	metric
ADDED LENGTH	.280 in	.71 cm
ADDED WEIGHT	2.61 oz	73.92 g

*Weights and dimensions may vary based on manufacturing tolerances.