



**RADICAL DEFENSE**

CAGE: 8RC72 » DUNS: 043893696

CALIBER 7.62

LENGTH 7.5"

## LS3 SUPPRESSOR

3D printed monolithic design using a nickel based Super Alloy Haynes 282, the LS-3 is one of the most durable suppressors on the market to date. The LS-3 is capable of sustained full-automatic fire while providing operators with sound, thermal, and flash mitigation. A semi-auto rated version is also available in Ti6Al4V.

The LS-3 utilizes a forward venting monolithic design controlling cyclic rate while the assist ports reduce back pressure. The LS-3 is protected by a high-temp Cerakote coating, providing protection and a higher level of concealability. Alphatek Alphashield IR Reflective coating available.

- Complete Signature Reduction
- Heat Resistant 3D-Printed Design
- Minimal Point-of-Impact Shift

### PRODUCT DETAILS

Specifications subject to change

CALIBER	7.62mm
MATERIAL	Haynes 282 or Ti64
COATING	Alphatek Alpha Shield IR
ATTACHMENT	1.375-24 HUB Mount

SUPPRESSOR*	WEIGHT	LENGTH	DIAMETER	HUB MOUNT*	WEIGHT	LENGTH
	17.5 oz / 12.75 oz (Ti)	7.5 in	1.6 in		2.61 oz	.280 in
	.50 kg / 0.36 kg	190.5 mm	40.64 mm		73.92 g	7.11 mm

\*Weights and dimensions may vary based on manufacturing tolerances.

SKU	UPC
LS3	814034027526
LS3 Ti	814034028363

### FLAT FRONT PLATE DESIGN



### MODULAR HUB MOUNT



### KFM TAPER LOCK FLASH HIDER / RD HUB MOUNT INCLUDED



This document contains privileged and/or confidential information belonging to Radical Defense and is intended only for the use of the intended recipient. In addition, it may contain technical data as defined in the International Traffic in Arms Regulations (ITAR) 22 CFR 120.10. Export of this material is restricted by the Arms Export Control Act (22 U.S.C. 2751 et seq.), as well as other laws, and it may not be exported or transferred to non-U.S. persons without prior written approval from the U.S. Department of State.